

C9010-022.exam.47q

Number: C9010-022
Passing Score: 800
Time Limit: 120 min
File Version: 1



Website: <https://vceplus.com>
VCE to PDF Converter: <https://vceplus.com/vce-to-pdf/>
Facebook: <https://www.facebook.com/VCE.For.All.VN/>
Twitter : https://twitter.com/VCE_Plus

<https://vceplus.com/>

IBM C9010-022

IBM AIX Administration V1

Exam A

QUESTION 1

How does PowerSC simplify security compliance and strengthen security?



<https://vceplus.com/>

- A. By integrating with IBM X-Force to receive security updates
- B. By encrypting SRIOV adapter traffic
- C. By providing trusted system extensions
- D. By creating central repository of users

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation: PowerSC simplifies security compliance and strengthens security by providing trusted system extensions.

Reference: http://www-01.ibm.com/common/ssi/ShowDoc.wss?docURL=/common/ssi/rep_sm/s/897/ENUS5765-PTS/index.html&lang=en&request_locale=en

QUESTION 2

A customer has a virtualized system using Virtual I/O Server with multiple client partitions accessing the SAN using NPIV?

Which command on the client partition should be run to retrieve the network address of the fiber adapter?

- A. `lscfg-vp -l fcs0`
- B. `lspci -vafcsi | grep "Network Address"`
- C. `lspath -npiv fcs0 | grep "Network Address"`
- D. `lsdev | grep fcs0`



Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 3

Where is a Cluster Aware AIX cluster configuration data stored?

- A. A NFS filesystem that is accessible by all nodes
- B. A shared disk that is accessible from all nodes.
- C. A master copy on one node and the data is replicated to the local disk of the other nodes
- D. A shared system pool that is accessible by all nodes

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Explanation: The cluster repository disk is used as the central repository for the cluster configuration data. The cluster repository disk must be accessible from all nodes in the cluster and is a minimum of 10 GB in size. Given the importance of the cluster configuration data, the cluster repository disk should be backed up by a redundant and highly available storage configuration.

Reference: https://www.ibm.com/developerworks/community/blogs/cgaix/entry/cluster_aware_aix1?lang=en

QUESTION 4

How can a system administrator verify the progress of an AIX client installation from the NIM master?

- A. `nim-o check <client>`
- B. `lsnim -l<client>`
- C. `nim -status <client>`
- D. `tail -f /var/adm/ras/nimclient_<client>`

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 5

What is the minimum version of AIX that is supported as a Versioned WPAR on an AIX 7.1 system?



<https://vceplus.com/>

- A. AIX 5.3 TL12 SP4
- B. AIX 5.2 TL10 SP8
- C. AIX 6.1 TL3 SP2
- D. AIX 5.1 ML8

Correct Answer: B
Section: (none)
Explanation



Explanation/Reference:

QUESTION 6

The administrator cannot ping the hostname of any system on the local network, including LPARs in the same managed system that have virtual Ethernet adapters configured on the same subnet and VLAN.

What is the most likely cause of this problem?

- A. The Ethernet cable from the system to the switch is disconnected or faulty.
- B. The Shared Ethernet Adapter in the Virtual I/O Server in the managed system is not passing communication between virtual adapters and the network.
- C. The routing table has been flushed on the host and the default route is no longer configured.
- D. DNS is disabled and the /etc/hosts file on the host does not contain the addresses for the host names that are being pinged.

Correct Answer: D
Section: (none)

Explanation

Explanation/Reference:

QUESTION 7

What are the three basic elements of RBAC in AIX?

- A. Groups, Keys, and Access
- B. Users, Groups, and KeyStore
- C. Keys, Privileges, and Groups
- D. Roles, Privileges, and Authorizations

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: http://www.ibm.com/developerworks/aix/library/au-aix_rbac/

QUESTION 8

When attempting to log into a system, the administrator receives the message "All network ports in use."

How can this be resolved?

- A. Add the terminals tty0 through tty9 to the /etc/securetty file
- B. Use the *no* command to enable ipforwarding
- C. On the HMC, select the option "Reset Connection" for the server
- D. Use the *chdev* command to increase the number of pseudo-terminals

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 9

A VIO client will use NPIV to boot from the SAN and needs to be installed using NIM.

Which two methods can be used to gather the WWPN information? (Choose two.)

- A. Examine the NIM client properties.
- B. Boot the LPAR and run `lscfg -vlfcSx`
- C. Utilize the HMC command line tool, `lssyscfg`
- D. Log into the VIO servers and run `lscfg -vlfcSx`
- E. Check the LPAR properties from the HMC GUI

Correct Answer: CD

Section: (none)

Explanation

Explanation/Reference:

QUESTION 10

Which file needs to be modified to export a NFS file-system as read-only?



<https://vceplus.com/>

- A. `/etc/xtab`
- B. `/etc/rmtab`
- C. `/etc/security/exports`
- D. `/etc/exports`

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: https://www.centos.org/docs/5/html/Deployment_Guide-en-US/s1-nfs-server-config-exports.html

QUESTION 11

Which performance tool can be used to determine if any particular partitions of a logical volume are more heavily accessed than others?

- A. lplayout
- B. fileplace
- C. lvmstat
- D. sar

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 12

A failed integrated tape drive was physically replaced in a Power Systems server. Without performing any additional operations, the administrator attempts to use the device and receives this AIX error message:

AN ERROR OCCURRED WHILE WRITING TO THE STORAGE MEDIA
THE DEVICE IS NOT READY FOR OPERATION

What is the likely cause?

- A. The media inside the failed tape drive was not removed.
- B. The tape drive needs to be powered on before being used.
- C. The tape device microcode needs to be updated.
- D. The drive was replaced but the new device information was not configured.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 13

Which option will prevent users in the DBA group from logging in using telnet or rlogin?

- A. Remove the users in the DBA group from the `/.rhosts` file
- B. Change the `rlogin` group attribute to 'false'
- C. Disable the automatic start-up of the `telnetd` daemon
- D. Set the `rlogin` user attribute to 'false' for each user in the DBA group

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 14

An AIX instance was initially configured to communicate over a single network interface. The administrator plans to configure an EtherChannel using the existing network interface and an additional network interface.

What is the correct sequence of steps to implement this configuration?

- A. Remove the existing IP information
Add both interfaces as primary adapters
Configure the IP address
- B. Configure the same IP address on the additional interface
Add both adapters as primary adapters
Remove the existing default route
- C. Configure the existing interface as a primary adapter
Configure the additional interface as a backup adapter
- D. Add both adapters as primary adapters
Configure the IP address as an alias on the additional interface

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 15

Additional space is required in `/tmp` to allow `snmp` to run to completion. There is **NOT** enough unallocated space in `rootvg` to increase `/tmp` to the required size. There **IS** enough free space within a secondary volume group.

How can the file system configuration be updated to allow snap to run successfully?

- A. Use *mirrorvg* with the *-l* parameter to mirror just */dev/hd3* to the secondary volume group and extend the file system
- B. Create a new logical volume in the secondary volume group, then increase the */tmp* file system capacity with *extendfs*
- C. Create a new file system within the secondary volume group and mount it over */tmp/ibmsupt*
- D. Dynamically move */tmp* into the secondary volume group with *migratepv* and extend the file system capacity with *chfs*

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 16

Which command can be run to clean up a previous snap?

- A. `snap -c`
- B. `errlog -c`
- C. `snap -r`
- D. `errclear`



Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 17

What action will prevent the *nfsd* subsystem from activating at boot time?

- A. Remove the */etc/export* file
- B. Change the Action attribute from 'wait' to 'once' for the *rcnfs* line within the */etc/inittab*
- C. Disable `-a boot=no /usr/bin/nfsd`
- D. Update */etc/inetd.conf* to remove the call to *startsrc* for the NFS subsystem group

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 18

An administrator saved a change to the active profile of an LPAR.

When will the change take effect?

- A. Immediately after the profile is saved
- B. When the Rebuild Managed System task completes
- C. When the LPAR is shut down and re-activated
- D. When the admin reboots the LPAR from within AIX

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:



QUESTION 19

A customer wants to edit the CPU and memory settings in a template that is used in the environment.

How should this be accomplished?



<https://vceplus.com/>

- A. Edit HMC V7 system template
- B. Edit HMC V8 system template

- C. Edit HMC V7 partition template
- D. Edit HMC V8 partition template

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 20

An administrator wants to change an LDAP user to use local files to authenticate.

What should the administrator change?

- A. Registry attribute
- B. Kerberos server
- C. SYSTEM attribute
- D. LDAP server

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:



QUESTION 21

Which two components are required to support VLANs in an AIX partition? (Choose two.)

- A. IEEE 802.1Q capable switch
- B. IEEE 802.1Q compatible adapter and driver
- C. IEEE 802.11n compatible adapter
- D. IEEE 802.15.4 capable switch
- E. IEEE 802.3ad compatible interface

Correct Answer: AB

Section: (none)

Explanation

Explanation/Reference:

QUESTION 22

An LPAR is hosted on Power8 hardware.

How can an adapter assigned as “required” to that LPAR be removed with minimal downtime?

- A. Initiate the Add/Remove procedure from the ASMI
- B. Use the CHARM tool to remove the adapter
- C. Remove the device through *diag*, and DLPAR remove the adapter
- D. Remove the required setting in the profile, and DLPAR remove the adapter

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 23

An administrator wants to migrate data in a volume group from one set of disks to a new set of disks. No free disks are currently available within the volume group.

What must be done before migrating the data to the new disks?

- A. The new disks must be added to the volume group with *extendvg* and then migrate the data.
- B. The volume group must be imported to the new disks with *importvg*.
- C. The volume group must be varied off with *varyoffvg* before adding the new disks.
- D. The new disks must be formatted for a volume group with *chdev* and then extended.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

QUESTION 24

An administrator is attempting to recover the *sendmail.cf* file from the weekly *mksysb* backup.

The following output confirms that the file does exist within the mksysb backup:

```
Cluster 51200 bytes (100 blocks).
Volume number 1
Date of backup: Wed 20 Mar 21:17:26 2013
Files backed up by name
User root
 48015 ./tmp/sendmail.cf
 53278 ./usr/lpp/bos.net/bos.net.tcp.client/7.1.1.17/inst_root/etc/mail/sendmail.cf
 53234 ./usr/lpp/bos.net/inst_root/etc/mail/sendmail.cf
   0 ./usr/samples/tcpip/sendmail/cf
  997 ./usr/samples/tcpip/sendmail/cf/aixsample.mc
 2786 ./usr/samples/tcpip/sendmail/cf/mailserver.mc
 1259 ./usr/samples/tcpip/sendmail/cf/submit.mc
 48015 ./etc/mail/sendmail.cf
 47955 ./etc/mail/sendmail.cf-
 53547 ./etc/mail/sendmail.cf--
 48015 ./etc/mail/sendmail.cf,1355401616
   21 ./etc/sendmail.cf
 48015 ./lpp/save.config/etc/mail/sendmail.cf
   21 ./lpp/save.config/etc/sendmail.cf
files archived: 49674
```

```
Restore a File or Directory

Type or select values in entry fields.
Press Enter AFTER making all desired changes.

* Restore DEVICE          [Entry Fields]
* Target DIRECTORY       [/tmp/rootvg_mksysb]      +/
FILE or DIRECTORY to restore  [/tmp/]                /
(Leave blank to restore entire archive.)
VERBOSE output?          [yes]                +
Number of BLOCKS to read in a single input operation  []                #
Restore extended attributes? [yes]                +
```

Why does the SMIT panel above fail to find and restore the required file?

- A. The file to restore must be correctly delimited relative to the backup
- B. Extended attributes should not be restored for a symbolic link
- C. /etc/mail/sendmail.cf is a symbolic link to /etc/sendmail.cf
- D. The target directory must match the source directory

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 25

A volume group is mirrored to two external storage systems. One of the storage systems is rebooted for maintenance. After the storage system is up and available, lsvg shows a disk in a missing state:

```
datavg:
```

PV_NAME	PV STATE	TOTAL PPs	FREE PPs	FREE DISTRIBUTION
hdisk1	active	788	0	00..00..00..00..00
hdisk2	missing	788	0	00..00..00..00..00

Which command will change the PV STATE from missing to active?

- A. `cfgmgr -vlhdisk2`
- B. `syncvg -v datavg`
- C. `chdev -l hdisk2 -a state=active`
- D. `varyonvgdatavg`

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Reference: http://tariqnazir.tripod.com/aix/AIX_Commands.htm

QUESTION 26

A customer wants to restore amksysb using a NIM server while using the least amount of disk space possible.

Which set of actions does the customer need to take?

- A. Define mksysb resource, create lpp_source from mksysb resource
- B. Define mksysb resource, create spot from lpp_source resource C. Define mksysb resource, create spot from mksysb resource
- D. Define spot resource, create lpp_source from mksysb resource

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 27

A customer has plugged a notebook into the HMC1 port of a brand new POWER8 server. The customer is attempting to get to the ASMI menu.

Why is nothing being displayed on the notebook?

- A. The notebook is not set up to accept a DHCP address from the service processor.
- B. The notebook is configured for IPv4 and the service processor only communicates via IPv6.
- C. The notebook is not on the same subnet as the service processor.
- D. The notebook needs to be plugged into the HMC2 port for the ASMI menu to be displayed on the notebook.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 28

Given the following topas output:

```
Topas Monitor for host :
Ti
Interval: 2
EVENTS/QUEUES      FILE/TTY
Cswitch            187  Readch          0
Syscall            121  Writch          311
Reads              0   Rawin           0
Writes             0   Ttyout          311
Forks              0   Igets           0
Execs              0   Names           1
Runqueue           1.50  Dirbik          0
waitqueue          0.0

CPU      User%  Kern%  wait%  Idle%   Physc   Entc%
Total    0.2   1.6   0.0   98.1   0.01   3.17

Network  SPS   I-Pkts  O-Pkts   B-In   B-Out
Total    2.09K  6.00   1.50   346.0  1.76K

Disk     Busy%   SPS   TPS   B-Read  B-Writ
Total    0.8   46.0K  11.00  0       46.0K

FileSystem SPS   TPS   B-Read  B-Writ
Total      0     0     0       0

PAGING
Real.MB    1024
% Comp     59
% Noncomp  18
% Client   18

PgspIn     0
PgspOut    0
```

What does the Entc% value represent?



<https://vceplus.com/>

- A. Percentage of Ethernet consumed
- B. Performance statistics for all logical CPUs in the system
- C. Percentage of physical capacity consumed
- D. Percentage of entitled capacity consumed

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

Explanation: %Entc (percentage of entitled capacity)

Reference: http://www.tablespace.net/papers/topas_intro.html

QUESTION 29

How can an administrator use the logical volume information returned by the `lslv -m` command?

- A. To determine the current state of the logical volume
- B. To determine which physical partitions are free for use by the logical volume
- C. To determine which physical partitions are allocated to the logical volume
- D. To determine the amount of available (unused) space in the logical volume

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 30

The first line of a script is:

```
#!/usr/bin/perl
```

What will this do when the script is run?

- A. It will execute the file `/usr/bin/perl` before executing the script.
- B. It will load environment variables in the `/usr/bin/perl` file.
- C. It will interpret the script using Perl.
- D. It will set the value of the “perl” environment variable to the empty string.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

Explanation: `#!/usr/bin/perl` mean at the beginning of many Perl scripts. S

Reference: <http://perlmaven.com/hashbang>

QUESTION 31

Which type of resource is required for every BOS installation performed with NIM?

- A. bosinst_data
- B. script
- C. resolv_conf
- D. spot

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 32

What procedure can be used to recover an AIX system that will not boot due to a corrupted boot logical volume?

- A. Power on the system and enter SMS mode
Select Diagnostics and Problem Determination
Select the option to Recover Boot Logical Volume
- B. Boot the system into maintenance mode using amksysb
Select the System Backup and Install menu
Select the option to Recover Devices
- C. Boot the system into maintenance mode using AIX installation media
Select the Start Maintenance Mode for System Recovery menu and access the root volume group
Issue the *bosboot* command for the rootvg disk
- D. Boot the system into maintenance mode using amksysb
Select the Start Maintenance Mode for System Recovery menu and access the root volume group
Copy the */SPOT/dev/hd5* to */dev/hd5* and run *syncvgrootvg*

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 33

Which command will change the database object for the primary dump device to dumplv permanently?

- A. sysdumpdev -P -p /dev/dumplv

- B. sysdumpdev -d /dev/dumplv
- C. mkdumpdev -p /dev/dumplv
- D. sysdumstart -p /dev/dumplv

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:

Explanation: To permanently change the database object for the primary dump device to /dev/newdisk1, enter the following command:

```
sysdumpdev -P -p /dev/newdisk1
```

Reference: https://www-01.ibm.com/support/knowledgecenter/ssw_aix_61/com.ibm.aix.cmds5/sysdumpdev.htm

QUESTION 34

An administrator is tasked with enhancing the data availability and I/O load balancing for an AIX 7.1 system attached to IBM storage.

Which action will satisfy the requirement?

- A. Set the correct host type on the storage array and match the failover settings on the AIX instance.
- B. Adjust the health check interval attribute for each hdisk presented from the storage array.
- C. Install the appropriate path control module to work in conjunction with the native MPIO driver.
- D. Remove the native MPIO driver and replace with the appropriate path control module.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 35

Which action must be completed on the HMC when a Recovery state is discovered?

- A. Select Initialize Partition for the LPAR in Recovery state
- B. Select Recover Partition Data for the Managed System
- C. Select Configuration and Rebuild Managed System
- D. Select Configuration and Restore partition data

Correct Answer: D

Section: (none)

Explanation

Explanation/Reference:

QUESTION 36

Which statement about interim fix management is correct with regard to planned maintenance?

- A. If the updates include the official APAR, the update_all process will automatically uninstall the interim fix.
- B. The interim fix will be automatically committed as part of the update process.
- C. The interim fix must be manually committed prior to applying the updates.
- D. If the fileset associated with interim fix will not be updated, it still needs to be temporarily rejected.

Correct Answer: A

Section: (none)

Explanation

Explanation/Reference:



QUESTION 37

An administrator uses the 'no' command to change the tcp_sendspace network tunable to 262144. A few minutes later, the ifconfig command produces the following output:

```
en0: flags=5e080863,c0<UP,BROADCAST,NOTRAILERS,RUNNING,SIMPLEX,MULTICAST,GROUPRT,
64BIT,CHECKSUM_OFFLOAD(ACTIVE),PSEG,LARGESEND,CHAIN>
    inet 10.126.0.5 netmask 0xffffffff broadcast 10.126.0.255
        tcp_sendspace 131072 tcp_recvspace 65536 rfc1323 0
```

What additional action is needed?



<https://vceplus.com/>

- A. Run the no command again, specifying a permanent change.
- B. Change the tcp_sendspace interface specific network option for the device.
- C. Refresh the inetd subsystem.
- D. Use ifconfig to cycle the interface down and up.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:



QUESTION 38

Which configuration is a requirement when migrating an LPAR via LPM (Live Partition Mobility)?

- A. LPARs with dedicated I/O adapters can be migrated using LPM, provided the same dedicated I/O adapters are available on the destination system.
- B. Physical disk attributes for backing devices must have the same reservation policy set on both source and target VIO Servers.
- C. The destination system must have the same virtual adapter slots free on its VIO Server as the source system.
- D. The source and destination systems must be managed by different HMC devices.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 39

An administrator is trying to export a file system on a server to external clients.

How can the administrator determine if all required NFS services are currently active?

- A. *lsitabrcnfs*
- B. *lssrc -a*
- C. *nfsd -l*
- D. *ps -ef | grep nfsd*

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

Reference: [https://books.google.com.pk/books?id=4ua1AgAAQBAJ&pg=PA126&lpg=PA126&dq=ps+%E2%80%93ef+|+grep+nfsd&source=bl&ots=U6ShE16BRG&sig=InhxqB-](https://books.google.com.pk/books?id=4ua1AgAAQBAJ&pg=PA126&lpg=PA126&dq=ps+%E2%80%93ef+|+grep+nfsd&source=bl&ots=U6ShE16BRG&sig=InhxqB-LHuoO8NRKhAe_a0Khq3A&hl=en&sa=X&ved=0ahUKEwiK2v3sqsrKAhWDSI4KHW1dAfoQ6AEIRzAI#v=onepage&q=ps%20%E2%80%93ef%20|%20grep%20nfsd&f=false)

[LHuoO8NRKhAe_a0Khq3A&hl=en&sa=X&ved=0ahUKEwiK2v3sqsrKAhWDSI4KHW1dAfoQ6AEIRzAI#v=onepage&q=ps%20%E2%80%93ef%20|%20grep%20nfsd&f=false](https://books.google.com.pk/books?id=4ua1AgAAQBAJ&pg=PA126&lpg=PA126&dq=ps+%E2%80%93ef+|+grep+nfsd&source=bl&ots=U6ShE16BRG&sig=InhxqB-LHuoO8NRKhAe_a0Khq3A&hl=en&sa=X&ved=0ahUKEwiK2v3sqsrKAhWDSI4KHW1dAfoQ6AEIRzAI#v=onepage&q=ps%20%E2%80%93ef%20|%20grep%20nfsd&f=false)

QUESTION 40

Given the following information:

```
# lshwres -r mem -m Server1 --level sys -F curr_avail_sys_mem
61440
```

```
# lssyscfg -r prof -m Server1 -F lpar_name min_mem desired_mem max_mem
lpar1      20480      40960      65536
lpar2      10240      20480      65536
lpar3      5120       10240      65536
lpar4      5120       10240      65536
```

In which order should the LPARs be activated to ensure that **all** of them will start?

- A. lpar2lp
ar3
lpar1
lpar4
- B. lpar1lp
ar2
lpar3
lpar4
- C. lpar
4lpar 3
lpar 1
lpar 2
- D. lpar
2lpar 3
lpar 4

lpar 1

Correct

Ans

wer:

B

Section: (none)

Explanation



Explanation/Reference:

QUESTION 41

What is the purpose of using the *ssh-keygen -t dsa* command?

- A. To provide performance monitoring agents to monitor encrypted file systems
- B. To securely transfer files between AIX instances without a password prompt using ftp
- C. To allow a user to switch to the root user without knowing the root password
- D. To establish credentials for a secure connection between systems

Correct Answer: D

Section: (none) ExplanationC. -----2

D. -----6

Correct Answer: -----6

Explanation/Reference:

QUESTION 42

Which parameter of the mkwpar command results in the created Versioned WPAR being mobility aware?

- A. -ma
- B. -lam

Section: (none)

Explanation

Explanation/Reference:

QUESTION 43

Given the *svmon* output below:

```
db2serv:/ # svmon -G -O unit=MB
Unit: MB
```



```
-----
-----
available          size          inuse          free          pin          virtual
memory            131072.00     119046.45      106.55        9793.35      146371.58
                230.52      Ded
pg space          4096.00          3850.00

                work          pers          clnt          other
pin              5927.04          0            0            3866.31
in use          10371.58          33.1         13840.81
```


What can be determined from this output?

- A. The minfree tunable should be reduced to improve file cache page steals.
- B. Pinned memory has exceeded the defined threshold.
- C. Active Memory Sharing should be disabled.
- D. System memory is overcommitted.

Correct Answer: C

Section: (none)

Explanation

Explanation/Reference:

QUESTION 44

How can ssh access to an AIX 7 system be restricted to the 192.168.0.1/24 subnet?

- A. Add the following entry to the hosts.allow file: sshd : *@192.168.0.1/24 Add the following entry to the hosts.deny file: sshd : ALL
- B. Add the following entry to the /etc/ssh/sshd_config file: AllowUsers *@192.168.0.*
- C. Set AIXPert to High Level Security
 - Add the AIXPertGroup xml tag in /etc/security/aixpert/core to 22
 - Add the AIXPertArgs xml tag in /etc/security/aixpert/core to allow=*@192.168.0.* deny=all
- D. Add the service filter through RBAC with mkauth id=192.168.0.* ssh

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 45

When defining a new NIM client, an administrator is prompted to select the type of network.

```

Define a Machine
Type or select a value for the entry field.
Press Enter AFTER making all desired changes.

Host Name of Machine [ttt@34p.ibm.com] [Entry Fields]
-----
Type of Network Attached to Primary Network Install Interface
Move cursor to desired item and press Enter.

tok = token ring network
ent  = ethernet network
fddi  = FDDI network
generic = generic network (no network boot capability)
atm   = ATM network
ent6  = IPv6 ethernet network
hfi   = HFI network

F1=Help      F2=Refresh      F3=Cancel
F8=Image     F10=Exit       Enter=Do
F5 /=Find    n=Find Next
  
```

Why does a NIM Master prompt for this confirmation?

- A. The nimesis service is not active on the client.
- B. A NIM network for the hosting subnet has not yet been defined.
- C. There is not Network Install Routing object to list the route to the adjacent subnet.
- D. The NIM Master's Primary Interface has not been initialized.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:

QUESTION 46

In which two ways can the pre-login message for an AIX LPAR be changed? (Choose two.)

- A. Issue the *chsys* command
- B. Edit the */etc/security/login.cfg* file
- C. Change the */etc/motd* file

- D. Use the `chsec` command
- E. Modify the `/etc/security/environ` file

Correct Answer: BC

Section: (none)

Explanation

Explanation/Reference:

QUESTION 47

What is the most likely cause of the following error when configuring a system?

```
root@db2prod:/ # cfgmgr
Method error {/usr/lib/methods/cfgfscsi -1 fscsi1 } :
    0514-061 Cannot find a child device.
```

```
root@db2prod:/ # lsdev -Cc adapter
ent0          Available          Virtual I/O Ethernet Adapter (1-lan)
ent1          Available          Virtual I/O Ethernet Adapter (1-lan)
fcs0          Available 00-00 8GB PCI Express Dual Port FC Adapter (df1000f114108a03)
fcs1          Available 00-01 8Gb PCI Express Dual Port FC Adapter (df1000f114108a03)
```

- A. The auto-negotiation setting is disabled.
- B. The HBA port at `fcs1` is not cabled.
- C. The RECOVERY policy on `fscsi1` has been set to disabled.
- D. The SDD multipath software has not been installed.

Correct Answer: B

Section: (none)

Explanation

Explanation/Reference:



<https://vceplus.com/>

